

DA9.2

2-Channel High-Performance Class-D Amplifier



Applications

- High-output full-range loudspeakers
- High-output subwoofer amplification
- Touring and rental production systems
- Nightclubs, DJs, and live venues
- Houses of worship and performance spaces
- Medium to large venues and high-output systems

Overview

The Sound Barrier DA9.2 is a high-power 2-channel Class-D amplifier engineered for demanding professional audio applications requiring increased output, efficiency, and reliability.

Designed with advanced switching power supply and active Power Factor Correction (PFC), the DA9.2 delivers powerful and consistent performance while maintaining high efficiency and reduced thermal load. Its high power per channel makes it ideal for driving subwoofers and large-format loudspeaker systems in both touring and installed environments.

With selectable gain settings, multiple operating modes (Stereo, Bridge, Mono), and comprehensive protection circuitry, the DA9.2 ensures stable operation even under high-load conditions.

Features

High Output Performance

- High power per channel for demanding applications
- Ideal for subwoofers and high-output speaker systems
- Stable performance under heavy load conditions

Efficient Class-D Design

- Advanced Class-D topology with >80% efficiency
- Reduced heat generation and lower operating costs
- Lightweight compared to traditional amplifiers

Advanced Power Supply

- 100–240V universal power input
- Active Power Factor Correction (PFC)
- Stable global operation with improved energy efficiency

Flexible System Integration

- Stereo, Bridge, and Mono operating modes
- Selectable gain settings (26dB – 41dB)
- Compatible with a wide range of signal sources and DSP systems

Tour-Ready Construction

- Rugged chassis for touring and installation
- Ideal for mobile racks and fixed installs

Cooling & Reliability

- Front-to-rear airflow cooling system
- Temperature-controlled fans
- Thermal protection with auto-recovery

Comprehensive Protection

- Over-temperature protection
- DC protection
- Short circuit protection
- Overload limiter
- Undervoltage protection

Sound Barrier USA
6935 NW 51 Street
Miami FL 33166, USA

Telephone: +1 305 594 3929
Email: sales@soundbarrier.com
www.soundbarrier.com



DA9.2

2-Channel High-Performance Class-D Amplifier

Channel Handling	
Number of output channels	2 x Speakon Type (NL4)
Number of input channels	2 x Balanced XLR inputs
Operating modes	Stereo / Mono / Bridge
Bridgeable output channels	One Bridged Pair Possible
Minimum load: Stereo / Mono	2Ω minimum
Minimum load: Bridge	4Ω minimum
Audio	
Gain	Selectable 41dB / 38dB / 35dB / 32dB
Input sensitivity at 41dB gain	1.38V RMS
Input sensitivity at 38dB gain	1.95V RMS
Input sensitivity at 35dB gain	2.75V RMS
Input sensitivity at 32dB gain	3.89V RMS
Default gain	typical: 0.01% (10% rated power, 8Ω)
Damping factor @ 8Ω	> 5000 (8Ω, 20Hz–200Hz)
Frequency response	Typical: +0 / -0.5dB (10% rated power, 20Hz–20kHz, 8Ω)
Crosstalk	≥90dB (20Hz–1kHz, below rated power)
THD+N	Typical: 0.01% (10% rated power, 8Ω)
Input impedance	20kΩ balanced / 10kΩ unbalanced
Signal LED threshold	Green when input signal is greater than -32dB
Clip / limiter indication	Yellow when output distortion is >1% or power is compressed
Output Stage	
Rated output power @ 8Ω Stereo	2 x 3000W
Rated output power @ 4Ω Stereo	2 x 5000W
Rated output power @ 2Ω Stereo	2 x 6500W
Rated output power @ 16Ω Bridge	1 x 6000W
Rated output power @ 8Ω Bridge	1 x 10000W
Rated output power @ 4Ω Bridge	1 x 13000W
Output RMS voltage	154.8V RMS
Output connector type	Speakon Type (NL4)
AC Mains Power	
Nominal AC input (±10%)	100–240 V @ 50/60Hz
Power supply design	Universal Switching Power Supply
Power factor correction	Active PFC (Power Factor Correction)
Power cord gauge	12 AWG
Idle consumption / standby input power	130W

Power Consumption & Heat	
Standby line current	0.6A @ 220V / 1.2A @ 110V
Standby power in / out / dissipated	130.0W / 0.0W / 130.0W
1/8 power @ 8Ω/ch line current	4.7A @ 220V / 9.5A @ 110V
1/8 power @ 8Ω/ch power in / out / dissipated	1041.7W / 750.0W / 291.7W
1/8 power @ 4Ω/ch line current	7.8A @ 220V / 15.7A @ 110V
1/8 power @ 4Ω/ch power in / out / dissipated	1723.0W / 1275.0W / 448.0W
1/3 power @ 8Ω/ch line current	11.2A @ 220V / 22.4A @ 110V
1/3 power @ 8Ω/ch power in / out / dissipated	2469.1W / 2000.0W / 469.1W
1/3 power @ 4Ω/ch line current	18.8A @ 220V / 37.7A @ 110V
1/3 power @ 4Ω/ch power in / out / dissipated	4146.3W / 3400.0W / 746.3W
Thermal	
Operating temperature	32°F – 104°F (0°C – 40°C)
Cooling	Front-to-rear Airflow
Fan control	Temperature-controlled fan
Thermal limiting threshold	185°F (85°C)
Thermal shutdown threshold	194°F (90°C)
Side clearance requirement	2.0 in (5cm)
Rear clearance requirement	3.9 in (10cm)
Construction	
Dimensions (W x H x D)	19.02 x 1.77 x 18.31 in (483 x 45 x 465 mm)
Rack width	19.02 in (483 mm)
Height	1.77 in (45 mm)
Depth	18.31 in (465 mm)
Rack space	1U
Net weight	29 lb (13 kg)
Included accessories	Power cord, user manual, 4 rubber feet
Signal-sensitive equipment spacing	7.9 in (20cm) minimum preferred
Protection circuits	Under voltage, DC, over temperature, overload, short circuit
Limiter functions	Over-temperature limiter, overload limiter, short limiter
PWR LED green	Power switch on
PWR LED yellow	Temperature limiter active
SIG LED green	Input signal greater than -32dB
SIG LED yellow	Output distortion >1% or power compression
SIG LED red	Protection condition

Sound Barrier USA
6935 NW 51 Street
Miami FL 33166, USA

Telephone: +1 305 594 3929
Email: sales@soundbarrier.com
www.soundbarrier.com

